TRIDELITY AG
Industriestr. 21
D-78112 St.Georgen / Germany
TEL:+49(0)7724.859806-00 / FAX:-99
info@tridelity.de / www.tridelity.de

datasheet

super slim
autostereoscopic
portrait mode
Multi-View 3D-Display

MP5520va



Optical	Size (diagonal)	139cm / 55"
	Size (active area)	680 x 1209 mm
	Format	9:16 portrait
	3D-views	5
	3D-technology	parallax-barrier
	Optimal viewing distance	approx. 2,5m / 8,5 ft
	Pixel per view	1,24 Mio subpixels (=> 2,5 Mio subpixels per user)
	Native resolution (total)	FullHD (1920 x RGB x 1080 Pixel)
	Native brightness of panel	600cd/m² max. Edge-LED backlight
	Response time (ton+toff)	8 ms typ. (grey to grey)

Physical	Outer Dimensions (W x H x D)	724 x 1252 x 62 mm
	Weight	38 kg
	Housing	Black metal housing bezel width: approx. 19 mm
	Table stand	*Contact TRIDELITY for available mounting solutions*
	Wall mounting	VESA 300 x 300 (M6)
	Operating conditions	+ 5° - +40° C 20%-80% rel. humidity (non-condensing) **Upright standing orientation only!**
	Storage & transportation conditions	-10° - +60° C 10% - 90% rel. humidity (non-condensing) **Upright standing orientation only!**

TRIDELITY AG
Industriestr. 21
D-78112 St.Georgen / Germany
TEL:+49(0)7724.859806-00 / FAX:-99
info@tridelity.de / www.tridelity.de

Electrical	Power input	100V - 240V AC 3,2A max 50/60Hz
	Power consumption	250 W max. < 1W (StdBy)
	Signal inputs	DVI-D (HDCP) HDMI (HDCP) DisplayPort (HDCP) analog HD-15 *(not for 3D signals)* S-Video *(not for 3D signals)*

miscellaneous	Accessories	power cord DVI signal cable User Manual
	Optional available accessories	Wall mounting
	Approvals	CE / FCC / cQPSus intended
	Software compatibility	Please contact TRIDELITY for detailed information
	Package dimensions (W x H x D)	1425 x 920 x 255 mm
	Package weight	46 kg

errors excepted / subject to change without notice

© 2011-2012 TRIDELITY AG