TRIDELITY AG
Industriestr. 21
D-78112 St.Georgen / Germany
TEL:+49(0)7724.859806-00 / FAX:-99
info@tridelity.de / www.tridelity.de

datasheet



autostereoscopic Multi-View 3D-display

MV4210va

Optical	Size (diagonal)	106cm / 42"
	Size (active area)	930 x 523 mm
	Format	16:9 widescreen
	3D-views	5
	3D-technology	parallax-barrier
	Optimal viewing distance	approx. 3,5 m
	Pixel per view	1,24 Mio subpixel
	Native resolution (total)	Full HD (1920 x 1080 RGB-Pixel)
	Native brightness of panel	700cd/m² typ.
	Native contrast ratio	3500:1
	Native colors of panel	16,7 Mio (8bits RGB)
	Response time (ton+toff)	4,5 ms typ. (grey to grey)

Physical	Outer Dimensions (W x H x D)	986 x 579 x 160 mm (with VESA) 986 x 630 x 275 mm (with stand)
	Width of frontbezel	25mm
	Weight	approx. 33 kg (with VESA OR stands)
	Wall mounting	VESA 400 x 400 (M6) (detachable)
	Table stand	Optional available VESA mounting has to be detached
	Operating conditions	+ 5° - +35° C 10%-80% rel. humidity (non-condensing) upright-standing direction
	Transportation & storage conditions	-10° - +60° C 10% - 80% rel. humidity (non-condensing) upright-standing direction

TRIDELITY AG
Industriestr. 21
D-78112 St.Georgen / Germany
TEL:+49(0)7724.859806-00 / FAX:-99
info@tridelity.de / www.tridelity.de

Electrical	Power input	100V - 240V AC / 5A 50 - 60Hz
	Power consumption	230 W typ. 15 W (Std.by)
	Signal inputs	DVI-D analog HD-15 (not for 3D signals intended)

miscellaneous	Accessories	Power cord DVI signal cable user manual
	Optional available accessories	Table stands
	Approvals	CE / FCC cQPSus *(safety mark USA & Canada)*
	Software compatibility	Please contact TRIDELITY for detailed information
	Package dimensions (W x H x D)	1130 x 740 x 370
	Package weight	approx. 40 kg

errors excepted / subject to change without notice

© 2011TRIDELITY AG